

## FIP13G

### 4-Line GigaE IP Phone

FIP13G is a 4-Line business IP phone specially for office staff who are looking for easy-to-use device. The 2.8" colour LCD display provides detailed call information accompanied by icons to maximize usability. Functions and contacts can be accessed quickly via 9 DSS/BLF keys. FIP13G provides users the newly designed LCD screen, as well as dual-port Gigabit Ethernet, PoE and 2.4GHz Wi-Fi.



### Key Features and Benefits

#### Simple and Easy to Use UI Design

FIP13G comes with a simple design yet ergonomic design that is easy to use. Prompts guide you through a simple installation process making it easy to start a voice collaboration.

#### Rich Features, Meet Your Needs

FIP13G supports dual 10/100/1000 Mbps ports and built-in 2.4GHz Wi-Fi, connect people with the way you like. The built-in USB port allows you to record calls onto a USB flash drive. Besides, FIP13G supports EHS Headset.

#### HD Voice Quality

FIP13G provides excellent voice quality. We have created high-definition sound quality solutions for handset and hands-free scenarios, even in a noisy environment.

#### High Security and Compatibility

All conversations are well protected. We make sure of security algorithms such as configuration files utilising AES, SRTP and TLS call encryption. The FIP1X series IP phones are widely compatible with SIP-based PBX platforms such as Asterisk, Broadsoft and 3CX.

- 2.8" 320 x 240px color display
- 4 SIP accounts
- 9 DSS/BLF keys
- HD Voice
- Opus
- 2 x Gigabit Ethernet port
- 1 x USB port
- PoE
- Stand with 3 adjustable angles
- EHS headset, RJ9 headset
- 2.4G Wi-Fi
- Wall mountable

## Audio Features

- > HD voice: HD handset, HD speaker
- > Wideband Codec: G.722, Opus, AMR-WB(Optional), G.711WB(Optional)
- > Narrowband Codec: G.711(A/u), iLBC, G.729AB, G.723, G.726, AMR-NB(Optional)
- > DTMF: In-band, RFC 2833 and SIP info
- > Full-duplex hands-free speakerphone
- > VAD, CNG, AEC, PLC, AJB, AGC

## Phone Features

- > 4 SIP accounts
- > Call hold, mute, DND, redial, auto answer
- > One-touch speed dial, hotline, SIP message
- > Call forward, call waiting, call transfer (attended/blind)
- > Paging, intercom, 3-Way conferencing, Dial rule
- > Direct IP call without SIP proxy
- > Set date time manually or automatically
- > IP conflict detection
- > 2.4 GHz Wi-Fi
- > Up to 9 DSS/BLF keys
- > USB port (2.0 compliant) for USB call recording

## Directory

- > Phone book (2000 records)
- > Black list
- > XML/LDAP remote phonebook
- > Phonebook search/import/export
- > Call history: dialed/received/missed (60 records)

## IP-PBX Features

- > BLF
- > Anonymous call, anonymous call rejection
- > Voice mail, call park, call pickup
- > Message waiting indicator (MWI)

## Feature Keys

- > 4 Line keys
- > 7 features keys: message, headset, hold, mute, transfer, redial, hands-free speakerphone
- > 4 Soft Keys
- > 5 Navigate Keys
- > Volume+/-

## Display and Indicator

- > 2.8" 320 x 240px color screen with backlight
- > 16 bit depth color
- > LED for call and message waiting indication
- > Dual-color (red/green) illuminated LEDs for line status information
- > Intuitive user interface with icons and soft keys
- > Multilingual user interface
- > Caller ID with name and number
- > Power saving

## Interface

- > 2x RJ45 Ports (Ethernet 10/100/1000 Base-T)
- > Support PoE
- > 1 x RJ9 Handset port
- > 1 x RJ9 Headset port
- > 1 x USB 2.0 port
- > 1 x Power adapter

## Management

- > Configuration: browser/phone/auto-provision
- > TFTP/HTTP/HTTPS for Auto Provisioning
- > TR069 (TR104/TR106)
- > Reset to factory, reboot
- > Package tracing export, system log
- > DNS/DNS SRV (RFC 1706, RFC 2782)
- > NAPTR for SIP URI lookup (RFC 2915)
- > Cloud device management: FCMS
- > DHCP server and DHCP client

## Others

- > Color: Classic grey
- > Stand with 3 adjustable angles
- > Wall mountable
- > AC/DC Adapter  
AC Input: 100~240V, 50~60Hz  
DC Output: 5V, 1A
- > Power consumption(PSU): 1.5-3.5W
- > Power consumption(PoE): 1.9-4.5W
- > Dimension (W x H x D x T) :  
190mm x 188.5mm x 173mm x 41.5mm
- > Relative humidity: 10%~90% (No Condensing)
- > Storage temperature: -25~ 65°C
- > Operation temperature: 0~45°C

## Network and Security

- > SIP v1 (RFC2543), v2 (RFC3261)
- > Call server redundancy supported
- > NAT Traversal By STUN
- > Proxy mode and peer-to-peer SIP link mode
- > IP assignment: Static IP and DHCP
- > HTTP/HTTPS web server
- > Time and date synchronization using SNTP
- > SDP (RFC 2327) , UDP/TCP
- > Mutil-VLAN, DSCP and 802.1p QoS
- > S RTP
- > TLS
- > HTTPS certificate manager
- > AES encryption for configuration file
- > Digest authentication
- > VPN: PPTP, L2TP, OpenVPN
- > IPv4 /IPv6 ,Dual stack IPv4/IPv6
- > RTP/RTCP (RFC 1889, RFC 1890)
- > ARP/RARP (RFC 826/903)
- > IEEE802.1Q VLAN/802.1p/DSCP
- > SNMPv2
- > LLDP/CDP/DHCP VLAN




## Package Contents

- > Flyingvoice FIP13G IP Phone
- Handset with handset cord
- Ethernet cable
- Stand
- Quick start guide
- > Qty/CTN: 10 PCS
- > N.W/CTN: 9.62 kg
- > G.W/CTN: 10.12 kg
- > Giftbox size: 270mm x 190mm x 78mm
- > Carton meas: 420mm x 420mm x 290mm

## Certified by



## Compatible with



## About Flyingvoice

Flyingvoice is a leading manufacturer of VoIP phones, ATA& gateways and VoIP routers. These products are preferred globally by international carriers, ITSP's, ISP's, corporate companies, and home users alike.

Driven by a need for ongoing innovation within VoWLAN technologies, Flyingvoice is committed to manufacturing products that allow for ease-of-installation scenarios within an enterprise network. Our people continuously improve existing products as well as expand upon product applications tailored to clients' requirements. These improvements ensure that your experience provides for secure, effective and efficient collaboration – anytime & anywhere.

## Copyright

Copyright © Flyingvoice Network Technology Co., Ltd. All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Flyingvoice Network Technology Co., Ltd.

## Technical Support

Visit [www.flyingvoice.com](http://www.flyingvoice.com) for product documents and FAQ, or contact Flyingvoice by email at [support@flyingvoice.com](mailto:support@flyingvoice.com). We'll get you the help you need.